



ProTeUS

Lackiergeräte und Zubehör für Profis



Kolbenpumpen

HIPPO

Hochvolumige Edelstahlpumpen ◀

LOW PRESSURE PAINT TRANSFER PUMPS

The range is suitable for transferring paint materials, oils, flammable liquids, to feed multiple spray guns and paint circulation systems. It is designed for high delivery up to 30 ltr./min.

FEATURES:

- ▷ Pneumatically sensed air motor
- ▷ High flow rate
- ▷ Stainless steel rust proof hydraulic body
- ▷ Easy maintenance
- ▷ Ice free air motors
- ▷ Light and easy to handle
- ▷ Compliance with EC norms

NIEDERDRUCK FARBVERSORGUNGSPUMPEN

Die Bandbreite ist ausgelegt, um Farben, Öle und brennbare Flüssigkeiten umzupumpen, sowie um mehrere Lackierpistolen oder Farbumlaufsysteme zu versorgen. Die Geräte sind entworfen für eine Förderleistung von bis zu 30 l/min.

BESONDERHEITEN:

- ▷ Pneumatisch gesteuerter Luftmotor
- ▷ Hohe Förderleistung
- ▷ Pumpenkörper aus rostfreiem Edelstahl
- ▷ Einfache Wartung
- ▷ Eisfreier Motor
- ▷ Einfache Handhabung
- ▷ Erfüllt die CE-Richtlinien



Type / Typ	1.170	3.400	4.400	6.400	12.400	1,5.900	3.900	5.900
Ratio	1:1	3:1	4:1	6:1	12:1	1,5:1	3:1	5:1
Output per cycle	170 cm ³	400 cm ³	400 cm ³	900 cm ³	400 cm ³	900 cm ³	900 cm ³	900 cm ³
Air motor diameter	diaphragm	80 mm	100 mm	125 mm	160 mm	80 mm	125 mm	160 mm
Stroke length	diaphragm	120 mm						
Recommended transfer Volume @25 cycles/min	4,25 ltr.	10,0 ltr.	10,0 ltr.	10,0 ltr.	10,0 ltr.	22,5 ltr.	22,5 ltr.	22,5 ltr.
Air inlet pressure max.	6 bar	6 bar	6 bar	6 bar	4 bar	6 bar	6 bar	6 bar
Output pressure max.	6 bar	18 bar	24 bar	36 bar	48 bar	9 bar	18 bar	30 bar
Air consumption @25 cycles/min (ltr./min)	30	180	240	450	750	180	450	750

► Options / Optionen

Stainless steel filter with ball valve
Edelstahlfilter mit Kugelhahn



Trolley + suction system
Wagen + Ansaugsystem

► All Type including / Inklusive

- ▷ air regulator ▷ Luftregler
- ▷ wall bracket ▷ Wandhalter
- ▷ silencer ▷ Schalldämpfer



